Driver and Event

Name

Date

Event

Weather

Result

Track Conditions

Grip Level

Surface

Track Condition

Temperature

Electrics

E.S.C

Servo

Reciever

Li-Po

Motor

Spur

Pinion

Internal Ratio

Wheels - Tyres - Inserts

Front Wheels

Front Inserts

Front Tyres

Rear Wheels

Rear Inserts

Rear Tyres

Transmission

Rear Diff Height

Front Diff Height

Front Layshaft Pulley

One Way ☐ Fixed ☐ F.A.B ☐

Front Drive

Front Overdrive

Chassis

Carbon Fibre ☐ S1 ☐

Notes

Rear Suspension

CATSx3

Pivot Pin Height: High ☐ Low ☐

Wheelbase: Short ☐ Medium ☐ Long ☐

Roll Bar: No ☐ 1.2 ☐ 1.4 ☐ 1.6 ☐





Equal Washers = 0° Toe-in
0.50 Difference = 0.65° Toe-in
1.00 Difference = 1.30° Toe-in
1.50 Difference = 1.95° Toe-in
2.00 Difference = 2.60° Toe-in
2.50 Difference = 3.25° Toe-in
3.00 Difference = 3.90° Toe-in

Note: The Anti-Squat Angle is worked out using the Toe-In Chart as the washers produce the same angles.



Toe-in / Rear Track Washers

Rear mm | Front mm | Actual °







Rear mm | Front mm | Actual °

Anti-Squat Washers

Front Suspension

Front Track Washers

Rear mm | Front mm





Front Rake: 10 Deg ☐ 7.5 Deg ☐



Roll Bar: No ☐ 1.2 ☐ 1.4 ☐ 1.6 ☐







Rear Shocks

Oil | Springs

Piston Holes: 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐

Diaphragm Spec



Front Shocks

Oil | Springs

Piston Holes: 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐

Diaphragm Spec

