SET-UP SHEET

X4'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4'26

RACE	Basic Set-Up For ASPHALT			
TRACK	Monsanto			
NAME	Alexander Hagberg	DATE		

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
		/sec	/	

TRACK

TRACK SURFACE		CARPET	☒ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☒ MIXED	☐ FAST
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL /cSt	☒ FRONT SOLID AXLE	GEAR DIFF OIL 7000 /cSt
UP ☒ ☐ DOWN	SOLID & DIFF POSITION	UP ☒ ☐ DOWN

PINION	SPUR GEAR	F. DRIVE RATIO
/T	110 /T	

SHOCKS

FRONT		REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /Cst	350
0	REBOUND %	0
☒ 4 HOLES ☐ PSS	☒ 1.1mm ☐ 1.2mm	☒ 1.1mm ☐ 1.2mm ☒ 4 HOLES ☐ PSS
SHOCK LENGTH 7.0 /mm		7.0 /mm SHOCK LENGTH

1.3	ANTI-ROLL BAR	1.2
THICKNESS/mm		THICKNESS/mm

FRONT		REAR
HUDY A1-36	TIRES	HUDY A1-36
HUDY Asphalt	ADDITIVE	HUDY Asphalt
10	ADDITIVE TIMING	10
	WIPE OFF TIME	
Timing: 10 Temp.: 75	TIRE WARMERS	Timing: 10 Temp.: 75

SIDE WALL GLUE DIA. /mm

FRONT TIRES ADDITIVE AREA /mm

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %

MOTOR	HW	TIMING	30
ESC	HW	BATTERIES	Team EAM
BODY	Xtreme Speciale	WING	Xtreme Twister

BODY POSITION

63 /mm Dimension from body post to window bottom line

7th hole, +1, o-ring

Dimension from body post to upper holder

WING SIDE PLATE ☒ YES ☐ NO

Dimension from edge to surface 65 /mm

WAVE BRACE: TOP DECK ☐, BULKHEADS ☒, NONE ☐

GF ☐ 1.6 ☐ 2.0 ☒ SCREWS ☒ 2.0 ☐ 1.6 ☐ GF ☒

SHIMS ☐☐

Rear used in front

2.0 ☐ 1.6 ☐

#301092 NONE ☐ BEARING ☐

CUTTING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER ☐ ☒ ☐ 5° 4° 3° — Adjust with eccentric bushings

Upper links CASTER

BUMP STEER 4.0 /mm

HEIGHT 19 /mm

SHIM 3 /mm

SHIM 3.0 /mm

0.5° 1.5° 2.5° 3.5° 4.5° 5.5° ☐ ☐ ☒ ☐ ☐ ☐ — Adjust with eccentric bushings

Upper links CASTER

1.5 /mm FF ☒ ☐ ☐

4.8 /mm RIDE HEIGHT

FR 1.5 /mm ☒ ☐ ☐

☒ SERVO SAVER ☐ SERVO HORN

TOE GAIN 3.0 /mm

2.0 /mm RF ☒ ☐ ☐

5.2 RIDE HEIGHT

RR 2.0 /mm ☒ ☐ ☐

FRONT

2.0 /degr. CAMBER Left=Right

BODY STOP YES ☒ ☐ NO /mm

SHIM /mm 0

FF 0 FR 0 SHIMS /mm 2.0

FRONT HUB: MEDIUM ☐ ☒ GRAPH. HARD ☐ ☐ ALU

#107730 Droop Gauge

#107712

DOWNSTOP /mm

Set with shocks ☐ ☐ Set without shocks

YES ☒ NO ☐ YES ☒ NO ☐ SUSPENSION FLEX

DRIVE SHAFT ☒ 58mm ☐ 59mm

SHIM /mm 0.5

0 UPSTOP/mm

23.6 DROOP /mm

Set with shocks ☒ ☐ Set without shocks

REAR

2.0 /degr. CAMBER Left=Right

BODY POST VERTICAL ☒ HORIZONT. ☐

SHIM /mm 1.0

RF 1.0 RR 1.0 SHIMS /mm 2.5

REAR HUB: MEDIUM ☐ ☒ GRAPH. HARD ☐ ☐ ALU

#107712

DOWNSTOP /mm

Set with shocks ☐ ☐ Set without shocks

YES ☒ NO ☐ YES ☒ NO ☐ SUSPENSION FLEX

DRIVE SHAFT ☐ 52mm ☒ 54mm

SHIM /mm 1.0

0 UPSTOP/mm

22.4 DROOP /mm

Set with shocks ☒ ☐ Set without shocks

FRONT TOP VIEW REAR

1.0 TOE OUT Left=Right

3.0 TOE IN Left=Right

ACKERMANN 0.5 /mm

SHORT LiPo BRASS WEIGHT YES ☐ ☒ NO YES ☐ ☒ NO

BRASS WEIGHT FOR MOTOR MOUNT

40g 40g

UPPER CLAMP ☒ KIT ☐ -1mm

UPPER CLAMP FLEX

SHIMS /mm

FRONT UPPER: CFF™ ARM - S ☒, LINKS SHORT ☐, LINKS LONG ☐

REAR UPPER: CFF™ ARM - S ☒, LINKS SHORT ☐, LINKS LONG ☐

STEERING BRIDGE ☐ YES ☒ NO

STEERING 7.5 SHIM SIZE

PLATE ☒ 8.0mm KIT ☐ 7.5mm

HUB OFFSET ☐ ☒ ☐ ☐ SHIM /mm

FRONT BOTTOM VIEW REAR

BUMPER: 3D - KIT ☒, FOAM ☐

STEER. LOCK 26 /degr.

T-BRACE: ALU ☐, BRASS ☐

SERVO HOLDER

MOTOR MOUNT

CHASSIS T-BRACE

CHASSIS: GRAPHITE ☒, ALU ☐, ALU 1.5mm ☐

FRONT ARMS: MEDIUM ☒, HARD ☐, SHORT ☐

REAR ARMS: MEDIUM ☒, HARD ☐, SHORT ☐

reset all