SET-UP SHEET

XRAY X4F'26

RACE

TRACK

NAME | DATE

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
			/sec	/	

TRACK

TRACK SURFACE		☐ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

TRANSMISSION

FRONT | REAR

GEAR DIFFERENTIAL - OIL /cSt

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO

SHOCKS

FRONT | REAR

XRAY SPRINGS

OIL /Cst

REBOUND %

☐ 4 HOLES ☐ PSS — ☐ 1.1mm ☐ 1.2mm — ☐ 1.1mm ☐ 1.2mm — ☐ 4 HOLES ☐ PSS

SHOCK LENGTH /mm | /mm SHOCK LENGTH

ANTI-ROLL BAR

THICKNESS/mm | THICKNESS/mm

	TIRES	
	ADDITIVE	
	ADDITIVE TIMING	
	WIPE OFF TIME	
Timing: Temp.:	TIRE WARMERS	Timing: Temp.:

SIDE WALL GLUE DIA. /mm

FRONT TIRES ADDITIVE AREA /mm

TOTAL WEIGHT /g	WEIGHT BALANCE	FRONT %	REAR %

MOTOR		TIMING		RPM LIMIT	
ESC		BATTERIES			
BODY		WING			

BODY POSITION

/mm Dimension from body post to window bottom line

/mm Dimension from body post to upper holder

WING SIDE PLATE ☐ YES ☐ NO

Dimension from edge to surface /mm

TOP DECK CUTTING

TOP DECK FLEX — 2.0mm ☐ ☐ 1.6mm

TOP DECK CUTTING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER 5° 4° 3° — Adjust with eccentric bushings

Upper links CASTER

BUMP STEER /mm | HEIGHT /mm | SHIM /mm

REAR CASTER 0.5° 1.5° 2.5° 3.5° 4.5° 5.5° — Adjust with eccentric bushings

Upper links CASTER

TOE GAIN /mm

/mm FF | RIDE HEIGHT /mm | FR /mm | ☐ SERVO SAVER ☐ SERVO HORN

/mm RF | RIDE HEIGHT /mm | RR /mm

FRONT SUSPENSION

/degr. CAMBER Left=Right

BODY STOP YES ☐ ☐ NO /mm

SHOCK HOLDERS SHIM /mm

FR /mm FF /mm SHIM /mm

FRONT HUB: ☐ MEDIUM ☐ HARD ☐ GRAPHITE ☐ ALU

SHIM /mm

SUSPENSION FLEX YES ☐ ☐ NO — YES ☐ ☐ NO

-3 -2 -1 0 1 2 3 4 5 6 7 8 9 10 HUDY

DRIVE SHAFT: 58mm 59mm | BEARING BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

/mm DOWNSTOP

Set with shocks ☐ ☐ Set without shocks

REAR SUSPENSION

/degr. CAMBER Left=Right

SHOCK HOLDERS FIXED ☐ ☐ ACTIVE SHIM /mm

RR /mm RF /mm SHIM /mm

REAR HUB: ☐ MEDIUM ☐ HARD ☐ GRAPHITE ☐ ALU

SHIM /mm

SUSPENSION FLEX YES ☐ ☐ NO — YES ☐ ☐ NO

-3 -2 -1 0 1 2 3 4 5 6 7 8 9 10 HUDY

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

/mm DOWNSTOP

Set with shocks ☐ ☐ Set without shocks

FRONT TOP VIEW REAR

TOE OUT Left=Right

TOE IN Left=Right

DIFF POSITION: UP ☐ ☐ +1mm DOWN ☐ STD. ☐

SHIMS /mm

Battery weight plate.

ARS LINKS SHIMS /mm

FRONT UPPER: ARM C ☐ XS ☐ S ☐ M ☐ | LINKS ☐

REAR UPPER: ARM C ☐ XS ☐ S ☐ M ☐ | LINKS ☐

ACKERMANN BUSHINGS

HUB OFFSET ☐ ☐ ☐ SHIM /mm

HUB OFFSET ☐ ☐ ☐ SHIM /mm

FRONT BOTTOM VIEW REAR

WEIGHT LEFT & RIGHT #309826 YES ☐ ☐ NO — 50g + 50g

STEER. LOCK /degr.

T-BRACE: ALU ☐ BRASS ☐

BUMPER WEIGHT YES ☐ ☐ NO — 100g

#302055 YES ☐ FRONT BRACE NO ☐

MOTOR MOUNT

CHASSIS T-BRACE

FRONT ARMS: MEDIUM ☐ HARD ☐ GRAPHITE ☐

CHASSIS: GRAPHITE ☐ ALU ☐

REAR ARMS: MEDIUM ☐ HARD ☐ GRAPHITE ☐

reset all