SET-UP SHEET

X4F'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'26

RACE	Basic - ETS - Asphalt
TRACK	
NAME	DATE

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
			/sec	/	

TRACK

TRACK SURFACE		☐ CARPET	☒ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☒ FAST
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH

TRANSMISSION

FRONT	REAR
GEAR DIFFERENTIAL - OIL: 200K /cSt	

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4,5

SHOCKS

FRONT		REAR
2,5 - 2,8	XRAY SPRINGS	2,6
350	OIL /Cst	350
0	REBOUND %	0
☒ 4 HOLES ☐ PSS	☒ 1.1mm ☐ 1.2mm	☒ 1.1mm ☐ 1.2mm ☒ 4 HOLES ☐ PSS
SHOCK LENGTH 8,5 /mm		8,5 /mm SHOCK LENGTH

ANTI-ROLL BAR

FRONT		REAR
1,3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1,6

	TIRES		
	ADDITIVE		
	ADDITIVE TIMING		
	WIPE OFF TIME		
Timing:	Temp.:	TIRE WARMERS	Timing: Temp.:

SIDE WALL GLUE
DIA. /mm

FRONT TIRES
ADDITIVE AREA /mm

TOTAL WEIGHT /g	WEIGHT BALANCE	FRONT %	REAR %

MOTOR		TIMING		RPM LIMIT	
ESC		BATTERIES			
BODY		WING			

BODY POSITION

/mm Dimension from body post to window bottom line

/mm Dimension from body post to upper holder

WING SIDE PLATE YES ☐ ☐ NO

Dimension from edge to surface /mm

TOP DECK CUTTING

TOP DECK FLEX

2.0mm ☐ ☐ 1.6mm

TOP DECK CUTTING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER ☐ ☒ ☐ 5° 4° 3°
Adjust with eccentric bushings
Upper links CASTER

BUMP STEER 2,5 /mm
HEIGHT /mm
SHIM /mm

REAR CASTER ☐ ☒ ☐ ☐ ☐ ☐ 0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
Adjust with eccentric bushings
Upper links CASTER

TOE GAIN 3 /mm

2 /mm FF ☒ ☐
5,0 /mm RIDE HEIGHT
FR 2 /mm ☐ ☐
☐ SERVO SAVER ☐ SERVO HORN

2 /mm RF ☒ ☐
5,2 /mm RIDE HEIGHT
RR 2 /mm ☒ ☐

FRONT SUSPENSION

2 /degr. CAMBER
Left = Right

BODY STOP YES ☐ ☐ NO /mm

SHOCK HOLDERS
SHIM 2 /mm

FR 1,5 /mm
FF 1,5 /mm
SHIM 3 /mm

FRONT HUB
MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

SHIM 0,5 /mm

SUSPENSION FLEX
YES ☒ ☐ NO
YES ☒ ☐ NO

DRIVE SHAFT
☒ 58mm ☐ 59mm
☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
5,4 /mm DOWNSTOP
Set with shocks ☐ ☐ Set without shocks

REAR SUSPENSION

2 /degr. CAMBER
Left = Right

SHOCK HOLDERS
FIXED ☒ ☐ ACTIVE
SHIM 2 /mm

RR 2 /mm
RF 2 /mm
SHIM 3 /mm

REAR HUB
MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

SHIM 1 /mm

SUSPENSION FLEX
YES ☒ ☐ NO
YES ☒ ☐ NO

#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
4,4 /mm DOWNSTOP
Set with shocks ☐ ☐ Set without shocks

FRONT TOP VIEW REAR

1 TOE OUT
Left = Right

2,5 TOE IN
Left = Right

DIFF POSITION
UP ☒ +1mm ☐
DOWN ☐ STD. ☒

SHIMS /mm
Battery weight plate.

ARS LINKS
SHIMS 5 /mm

FRONT UPPER
ARM LINKS
C ☐ ☐
XS ☒
S ☐
M ☐

REAR UPPER
ARM LINKS
C ☐ ☐
XS ☒
S ☐
M ☐

ACKERMANN BUSHINGS

HUB OFFSET ☒ ☐ ☐ SHIM /mm

HUB OFFSET ☒ ☐ ☐ SHIM /mm

FRONT BOTTOM VIEW REAR

WEIGHT LEFT & RIGHT #309826
YES ☒ ☐ NO

50g + 50g

STEER. LOCK 25 /degr.

T-BRACE
ALU ☐
BRASS ☐

BUMPER WEIGHT
YES ☐ ☒ NO
100g

#302055
YES ☐ FRONT BRACE ☒ NO

MOTOR MOUNT

CHASSIS T-BRACE

FRONT ARMS
MEDIUM ☒
HARD ☐
GRAPHITE ☐

CHASSIS
GRAPHITE ☒
ALU ☐

REAR ARMS
MEDIUM ☒
HARD ☐
GRAPHITE ☐

reset all