SET-UP SHEET

XRAY X4F'27

RACE			
TRACK			
NAME		DATE	
COUNTRY		CITY	

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
			/sec	/	

TRACK

TRACK SURFACE		☐ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

TRANSMISSION

GEAR DIFFERENTIAL - OIL	/cSt	DIFFERENTIAL POSITION	UP ☐ ☐ DOWN

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO	BEARING HOLDER
			KIT ☐ ☐ ALU

SHOCKS

FRONT	SHOCKS	REAR
	XRAY SPRINGS	
	OIL /Cst	
	REBOUND %	

☐ 4 HOLES ☐ PSS — 1.1mm / 1.2mm — 1.1mm / 1.2mm — ☐ 4 HOLES ☐ PSS

SHOCK LENGTH ____ /mm ____ /mm SHOCK LENGTH

ANTI-ROLL BAR

THICKNESS/mm ____ THICKNESS/mm

	TIRES	
	ADDITIVE	
	ADDITIVE TIMING	
	WIPE OFF TIME	
Timing: Temp.:	TIRE WARMERS	Timing: Temp.:

SIDE WALL GLUE — DIA. /mm

FRONT TIRES — ADDITIVE AREA /mm

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %

MOTOR		TIMING		RPM LIMIT	
ESC		BATTERIES			
BODY		WING			

BODY POSITION

/mm Dimension from body post to window bottom line

/mm WING SIDE PLATE YES ☐ ☐ NO

Dimension from body post to upper holder

Dimension from edge to surface /mm

FRONT REINFORCEMENT — TOP DECK FLEX — REAR REINFORCEMENT — TOP DECK CUTTING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER ☐ ☐ ☐ 5° 4° 3° — Upper links CASTER

Adjust with eccentric bushings

BUMP STEER /mm — HEIGHT /mm — SHIM /mm

REAR CASTER ☐ ☐ ☐ ☐ ☐ ☐ 0.5° 1.5° 2.5° 3.5° 4.5° 5.5° — Upper links CASTER

Adjust with eccentric bushings

TOE GAIN /mm

/mm FF — RIDE HEIGHT /mm — FR /mm

☐ SERVO SAVER ☐ SERVO HORN

/mm RF — RIDE HEIGHT /mm — RR /mm

FRONT

/degr. CAMBER Left = Right

BODY STOP YES ☐ ☐ NO /mm

SHIM /mm — PLAY /mm

FF / FR SHIMS /mm

FRONT HUB: MEDIUM ☐ ☐ GRAPH. / HARD ☐ ☐ ALU

#107730 Droop Gauge

10 9 8 7 6 5 4 3 2 1 0 -1 -2 -3 #107712

DOWNSTOP /mm — Set with shocks ☐ ☐ Set without shocks

YES NO YES NO SUSPENSION FLEX SCREW

DRIVE SHAFT ☐ ☐ 58mm 59mm

SHIM /mm — Set with shocks ☐ ☐ Set without shocks

DROOP /mm

REAR

/degr. CAMBER Left = Right

RF / RR SHIMS /mm

REAR HUB: MEDIUM ☐ ☐ GRAPH. / HARD ☐ ☐ ALU

SHIM /mm — PLAY /mm

10 9 8 7 6 5 4 3 2 1 0 -1 -2 -3 #107712

DOWNSTOP /mm — Set with shocks ☐ ☐ Set without shocks

YES NO YES NO SUSPENSION FLEX SCREW

SHIM /mm — Set with shocks ☐ ☐ Set without shocks

DROOP /mm

FRONT TOP VIEW REAR

TOE OUT Left = Right — TOE IN Left = Right

BUMPER WEIGHT YES ☐ ☐ NO — 30g

UPPER CLAMP KIT ☐ ☐ -1mm — UPPER CLAMP FLEX

SHIMS /mm — Battery weight plate. 9g

ARS LINKS POSITION — UPPER CLAMP FLEX

FRONT UPPER: CFF™ ARM ☐ / LINK SHORT ☐ / LINK LONG ☐

CHASSIS FLEX: NO BRACE ☐ / MEDIUM ☐ / STIFF ☐

REAR UPPER: CFF™ ARM ☐ / LINK SHORT ☐ / LINK LONG ☐

HUB OFFSET — SHIM /mm — ACKERMANN BUSHINGS — HUB OFFSET — SHIM /mm

FRONT BOTTOM VIEW REAR

WEIGHT LEFT & RIGHT YES ☐ ☐ NO

STEER. LOCK /degr.

#293085 TUNGSTEN WEIGHT 10g — 40g — 40g — FRONT BRACE

MOTOR MOUNT

T-BRACE: ALU ☐ / BRASS ☐ — CHASSIS T-BRACE

FRONT ARMS: MEDIUM ☐ / HARD ☐ / SHORT ☐

CHASSIS: GRAPHITE ☐ / ALU 1.5 ☐

REAR ARMS: MEDIUM ☐ / HARD ☐ / SHORT ☐